



**Product Data Sheet**

**ENGINE OIL HDX 25W-60**

**Product Description:**

**ENGINE OIL HDX 25W-60** is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

**ENGINE OIL HDX 25W-60** is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

**ENGINE OIL HDX 25W-60** exceeds the following performance criteria:

<b>Exceeds</b>	MB 228.3 API CI-4 JASO DH-1 DAF HP-2 CAT ECF-2	MAN M 3275 ACEA E7 Allison C4 Cummins CES 2077/20078 Renault RLD-2	Volvo VDS-3 DDC 93K215 MTU Type 2	MACK EO-N Global DHD-1 Mack EO-M+ API SL
----------------	--	--	---	---

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	25W-60
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	896
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	227
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	22.6
Viscosity Index		ASTM D2270	122
Viscosity CCS @-10°C, max	cP	ASTM D2270	8000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	10.7
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 4245

Date Issued:04-03-2015

Date Superseded: -

Revision nr: -