



Product Data Sheet

MONO ENGINE OIL CF 30

Product Description:

MONO ENGINE OIL CF 30 is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

Mono Engine Oil CF 30 is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

MONO ENGINE OIL CF 30 is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

MONO ENGINE OIL CF 30 exceeds the following performance criteria:

API SF/CF MTU Type 2 CCMC G2/D1 MIL-L-46152

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	30
Density@15°C	kg/m ³	ASTM D4052	893
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	104.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.5
Viscosity Index		ASTM D2270	99
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
Total Base Number	mgKOH/g	ASTM D2896	5.4

Product Nr: 4266

Date Issued: 12-03-2015

Date Superseded: 01-01-2015

Revision nr: 02