



**Product Data Sheet:**

# MONO ENGINE OIL CBSB 40

**Product Description:**

**MONO ENGINE OIL CBSB 40** is an engine oil developed to meet the requirements of a variety of older engines operating under severe conditions. **MONO ENGINE OIL CBSB 40** is formulated from highly refined mineral base stocks and balanced additives to provide effective protection to engines operating under various environments.

**MONO ENGINE OIL CBSB 40** is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.

**MONO ENGINE OIL CBSB 40** has improved detergency that helps to reduce deposits and keeps engines cleaner, better thermo-oxidative stability protects against sludge build-up, deposits & oil degradation and controls oil thickening. Effective antiwear properties protects engine components against wear to offer extended engine life and reduced maintenance costs and good corrosion inhibition properties protects against corrosion and wear.

**MONO ENGINE OIL CBSB 40** is suitable for naturally aspirated engines.

**Specifications:**  
**Exceeds: API CB/SB**

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J300	40
Density @ 15°C	ASTM D4052	895 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	144 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	14.5 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	95
Flash Point	ASTM D92	240°C
Pour Point	ASTM D97	-15°C
Total Base Number	ASTM D2896	2.8 mgKOH/g
Sulphated Ash	ASTM D874	0.38 wt %

Product nr: 4278

Date Issued: 20/01/2010

Date Superseded: -

Revision nr: -